

# EastCom 280 Technical Specification



## General

### Installation types

- Indoor, frontload or rear load
- Free standing, partly integrated

### Chassis

- Illuminated advertising light box
- Customers guided by optical indicators at all input and output modules

## Banknote processing

### Cash-out module

- Withdrawals of up to 60 notes in a bundle
- Banknote reject/bundle retract

### Banknote storage

- 2/4 cassettes
- Maximum fill level 310 mm
- Fill level indicator
- Scalable cassette concept: Lock, lead seal, tamper indicator
- Retract/reject cassette with 2 compartments

## Customer interaction

### Display

- 8,4" TFT LCD Display (Frontload version)
- 15" TFT LCD-Display
- 8 soft keys and/or touch display (Braille option)

### Keyboard

- EPP PCI certified
- EMV compliant
- Supports Remote Key Loading

### Card processing

- Motorized card reader LoCo/HiCo, track down magnetic read only, read/write Smart/IC card
- Motorized hybrid card reader HiCo 1, 2, 3; MTD USB, magnetic read/write, read/write Smart/IC card

- DIP card reader

### Printers

- Receipt printer (Thermal)
- Journal printer (Thermal or Impact)

### Audio

- Loudspeakers, headset jack with adjustable volume

## Security

### Cash security

- Safes: UL Business Hours, UL 291 Level 1, CEN L

### Data and software security

- Anti-Manipulation Card Slot
- Anti-Skimming II Module
- Awareness mirrors
- Privacy display filter for the monitor

### Identity and access control

- Mechanical and electronic locks
- Biometric options: Fingerprint
- Recessed PIN Pad
- Intelligent operator authentication

### Security monitoring

- Cash slot and portrait camera

## Multifunctionality

### Barcode reader

- 1D or 2D Barcodes

## Service

### Operator panel

- 8,4" graphical color display (RL only)

## Operation

### Environmental conditions

- Temperature range: +5 °C to +40 °C
- Humidity: 5 % to 85 %

### Technical details

- Supply voltage range: 110 – 120 V; 220 – 240 V
- Mains frequency 50/60 Hz
- Uninterruptable Power Supply

## Software

### Operating System

- Windows XP Professional SP3
- Windows POSReady2009

### Weight

- 200 kg (with UL Bus Hours)
- 400 kg (with UL safe)
- 460 kg (with CEN L safe)

